

# MOTO TRANSMISIONES 10W40



MOTORCYCLE

## Lubricants

### Description

Lubricant oil formulated for lubricating motorcycle gearboxes. It provides excellent resistance to shearing and ensures that oil bath clutches operate with perfect slipping control in extreme conditions. It prolongs the life of all gearbox components, reduces mechanical noise and helps cold starts..

### Properties

- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Provides optimum friction in clutch discs, preventing slippage.
- Enables speed and clutch changes to be carried out smoothly and precisely.

### Quality Levels

- JASO T-903:2011 MA & MA2

### Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.854
Viscosity at 100 °C	cSt	ASTM D 445	14.1
Viscosity at 40 °C	cSt	ASTM D 445	89
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	160
Flash point, open cup	°C	ASTM D 92	244
Pour Point	°C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	7.7
Sulphated ashes	% in weight	ASTM D 874	0.7

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 3 October 2014